



## ALUREX SPECIAL

### Removes surface rust and light dirt

- Removes surface rust and light dirt
- Contains no abrasives, does not damage surface
- Does not scratch glass or rubber
- Can be rinsed off with water
- Also suitable for stainless-steel, non-ferrous metals, and glass

# ALUREX SPECIAL

## BESKRIVELSE

Also removes light corrosion (surface rust), road and city grime, exhaust gas deposits, and industrial pollution. Suitable for stainless steel, bare and anodised aluminium, painted metal, and glass.

## ANBEFALET BRUG

Alurex Special Ready-to-Use is suitable for removing light corrosion, road and city grime, exhaust gas deposits, surface rust, industrial pollution, and so on, from painted metal, anodised aluminium, non-ferrous metals, glass, and stainless steel.

## PRAKTISK FORBRUG

Consumption is heavily dependent on the degree of dirt and corrosion.

## BRUGSANVISNING

Do not dilute Alurex Special Ready-to-Use.

Work from the bottom to the top to avoid runs and stripes.

Apply the product using a spray bottle and allow to soak in for at least 5 minutes.

If necessary, use a car brush, sponge, or white pad as an aid.

Also available in as a concentrate for use in a refill spray bottle. Dilute to the mixture ratio of 200 ml Alurex Speciaal Concentraat to 450 ml clean water. After use, rinse thoroughly with water until a neutral surface is obtained.

*First, try out a test surface.*

## ANVENDELSESBETINGELSER

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 25 °C

## RENGØRING AF UDSTYR/SPILD

Rinse with clean water immediately after use.

## BEMÆRKninger

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

1

## HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

**Udstedelsesdato:** 15/05/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95522 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)