



## UNIVERSOL® ECO

# Protects and degreases paintwork and more

- Effectively dissolves grease and dirt
- Post-wash unnecessary
- Improves adhesion
- Safe for the user and environment
- It is also very suitable as a concentrated all-purpose cleaner for dirty ovens, engines, floors, etc.

# UNIVERSOL® ECO

## BESKRIVELSE

The 100% ecological cleaner and degreaser for paintwork, stainless-steel surfaces, extremely grimy floors, industrial kitchens, etc.

## ANBEFALET BRUG

Universol® Eco is extremely suitable:

- For cleaning and degreasing all surfaces that will be painted. It is not necessary to rinse off afterwards, so you can immediately start painting.
- A highly-concentrated industrial all-purpose cleaner for cleaning light to heavily fouled surfaces.
- A stainless-steel cleaner.

## BRUGSANVISNING

Dilute Universol® Eco with water.

Recommended mixture ratio:

1: 25 for heavily fouled paintwork, ovens, engines, and stainless steel

1: 50 for fouled industrial kitchens, machines, and floors

1: 100 for lightly fouled paintwork and windows

Apply the diluted Universol® Eco concentrate with a sponge, cloth, or brush.

Allow to soak in for several minutes, then wipe with a sponge, cloth, or brush to activate and increase the action.

For stubborn dirt, allow it to soak in longer, possibly with a higher concentration. Remove with a moist cloth or sponge.

## ANVENDELSESBETINGELSER

Can be used in all circumstances, but do not apply in direct sunlight in frosty conditions.

## RENGØRING AF UDSTYR/SPILD

Rinse with clean water after use.

## PH

11,20

## HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

**Udstedelsesdato:** 15/05/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shandon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95522 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zellem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)