

**PROCHEMKO**



## **B-WAX**

# **Sacrificial anti-graffiti coating**

- Suitable for a wide variety of surfaces, porous, or smooth
- Virtually invisible
- Weather resistant
- Does not damage the environment
- Water permeable

# B-WAX

## POPIS PRODUKTU (DLOUHÝ)

It is a virtually invisible, environmentally-friendly, anti-graffiti and anti-poster coating based on natural waxes for all surfaces resistant to water from minimally 60 °C.

## DOPORUČENÉ POUŽITÍ

This is a sacrificial anti-graffiti coating for all mineral construction materials, natural stone, and other façade cladding.

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 1,02 kg/l  
Úroveň lesku: Satin

## DRY TIMES BY 20

Dotykem suché: N/A  
Suchý nátěr: N/A  
Plně vytvrzené: N/A

## TEORETICKÁ SPOTŘEBA

3 – 5 m<sup>2</sup> / l in a 2 layer system.

## NÁVOD K POUŽITÍ

Clean the surface with an appropriate Prochemko façade cleaning agent and allow the surface to dry.

Remove previously applied graffiti remover using Topper or Removex Green.

Spray off with water under high pressure.

Apply B-Wax on a dry surface using a brush, roller, or low-pressure hand spray.

For optimal results with a standard system, apply a second layer crosswise after a two-hour drying time.

Remove graffiti using high-pressure hot water minimally at 80 °C. Then apply the new system.

First apply Prochemko Grease Cleaner Foam to old layers of B-Wax. Then allow it to soak in for a few minutes. Now wipe all of it with a hard brush and remove with a high-pressure cleaner.

## PODMÍNKY POUŽITÍ

Minimum ambient temperature : 10 °C

Maximum relative humidity : 80%

Minimum surface temperature : 8 °C

Maximum surface temperature : 25 °C

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with clean water immediately after use.

## POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## DOBA POUŽITELNOSTI

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu