



COATEX SPECIAAL NV

Anti-graffiti coating in matt or gloss

- Very durable, scratch resistant, and chemically resistant
- Flexible and shock-resistant
- Does not yellow, UV resistant
- Available in matt and gloss, colourless, and with colour
- Colourless coating does not change the appearance of the surface



COATEX SPECIAAL NV

BESKRIVELSE

Polyurethane two-component scratch-resistant anti-graffiti coating with good chemical and mechanical resistance and colour fastness.

ANBEFALET BRUG

Coatex Special NV is a durable anti-graffiti system for objects that must comply with the strictest requirements in terms of chemical and mechanical resistance.

REMOVING GRAFFITI

- Apply Rodex to the surface to be cleaned.
- Apply Topper on the surface to be cleaned.
- Spray off with cold water (at maximally 35 bar)
- Treat the surface afterwards with Rodex diluted with water (1: 10)

TEKNISK DATA

Tæthed: 1,07 kg/l (transparant) - 1,36 kg/l (kleur)
Glansgrad: Blank,Mat
Tørstofindhold i volumen: 56% (transparant) - 57% (kleur)

PRAKTISK FORBRUG

Depends on many factors, such as porosity, roughness of the surface, and material loss when applying the paint.

BRUGSANVISNING

Vigorously mix A and B components in the correct proportion until a homogeneous mixture is achieved.

Dilute with Coatex Speciaal Thinner maximally 10%.

Apply Coatex Speciaal NV on a surface treated with Rust-Oleum 5401.

Apply the product using a brush, spray gun, or short-haired roller.

ANVENDELSESBETINGELSER

Minimum ambient temperature : 10 °C

Maximum relative humidity : 80%

Minimum surface temperature : 10 °C

Maximum surface temperature: 35 °C

RENGØRING AF Udstyr/SPILD

Coatex Special Thinner.

BEMÆRKNINGER

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

SIKKERHEDSDATA

VOC-niveau: 468 g/l
VOC-færdigblanding: 468 g/l
VOC-kategori: A/j
VOC-grænse: 500 g/l
Bemærkninger om sikkerhed: Consult the associated product safety leaflet and the information listed on the packaging.

HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Udstedelsesdato: 25/03/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu