



## CHALK-CEMENT-EX PUMPSPRAY

# Effortlessly removes lime and cement deposits

- Effective action and result
- For acid-resistant surfaces
- Wide range of use
- Can be rinsed off with water

# CHALK-CEMENT-EX PUMPSPRAY

## POPIS PRODUKTU (DLOUHÝ)

For the easy removal of old and hard lime and cement deposits from acid-proof surfaces. Also suitable for the removal of cement scum.

## DOPORUČENÉ POUŽITÍ

Chalk-Cement-Ex Pumpspray is suitable for removing lime and cement residues from a variety of acid-resistant surfaces. It is also suitable for use as an 'etching agent' for smooth cement-based floors, and so on, and as a descaler for pipes, boilers, etc.

## PRAKTICKÁ SPOTŘEBA

Consumption is heavily dependent on the level of dirt and the desired result.

## NÁVOD K POUŽITÍ

Chalk-Cement-Ex Pumpspray is ready for use. Spray on the contamination, brush through with a brush or white nylon pad and allow to work in for 5 minutes. Afterwards, rinse well with water. In case of stubborn soiling, repeat the treatment or allow the Chalk-Cement-Ex to work in for longer, possibly in a higher concentration. Refill the bottle with 150 ml of concentrate and 350 ml of water. Chalk-Cement-Ex is also available in 1, 5 and 10 litre concentrates.

## PODMÍNKY POUŽITÍ

Minimum ambient temperature: 5 °C

Maximum relative humidity: 100%

Minimum surface temperature: 5 °C

Maximum surface temperature: 35 °C

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with clean water immediately after use.

## POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## DOBA POUŽITELNOSTI

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu