



CHALK-CEMENT-EX PUMPSPRAY

Effortlessly removes lime and cement deposits

- Effective action and result
- For acid-resistant surfaces
- Wide range of use
- Can be rinsed off with water

CHALK-CEMENT-EX PUMPSPRAY

BESKRIVELSE

For the easy removal of old and hard lime and cement deposits from acid-proof surfaces. Also suitable for the removal of cement scum.

ANBEFALET BRUG

Chalk-Cement-Ex Pumpspray is suitable for removing lime and cement residues from a variety of acid-resistant surfaces. It is also suitable for use as an 'etching agent' for smooth cement-based floors, and so on, and as a descaler for pipes, boilers, etc.

PRAKTISK FORBRUG

Consumption is heavily dependent on the level of dirt and the desired result.

BRUGSANVISNING

Chalk-Cement-Ex Pumpspray is ready for use. Spray on the contamination, brush through with a brush or white nylon pad and allow to work in for 5 minutes. Afterwards, rinse well with water. In case of stubborn soiling, repeat the treatment or allow the Chalk-Cement-Ex to work in for longer, possibly in a higher concentration. Refill the bottle with 150 ml of concentrate and 350 ml of water. Chalk-Cement-Ex is also available in 1, 5 and 10 litre concentrates.

ANVENDELSESBETINGELSER

Minimum ambient temperature: 5 °C

Maximum relative humidity: 100%

Minimum surface temperature: 5 °C

Maximum surface temperature: 35 °C

RENGØRING AF Udstyr/SPILD

Rinse with clean water immediately after use.

BEMÆRKNINGER

Dispose of remnants of the product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Udstedelsesdato: 25/03/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu