



CHALK-CEMENT-EX CONCENTRATE

Effortlessly removes lime and cement deposits

- Effective action and result
- For acid-resistant surfaces
- Wide range of use
- Can be rinsed off with water

CHALK-CEMENT-EX CONCENTRATE

POPIS PRODUKTU (DLHÝ)

For the easy removal of old and hard lime and cement deposits from acid-proof surfaces.
Also suitable for the removal of cement scum.

ODPORÚČANÉ POUŽITIE

Chalk-Cement-Ex Concentrate is suitable for removing lime and cement residues from a variety of acid-resistant surfaces. It is also suitable for use as an 'etching agent' for smooth cement-based floors, and so on, and as a descaler for pipes, boilers, etc.

PRAKTIČKÁ VÝDATNOSŤ

Maximum dilution: 1:10. Consumption is heavily dependent on the level of dirt and the desired result.

NÁVOD NA POUŽITIE

Dilute Chalk-Cement-Ex Concentrate with water to maximally 1:10. In case of vertical surfaces, work from the bottom to the top to avoid runs and streaks. Apply the product using a sponge or hand spray gun and allow to soak in for 5 to 10 minutes. If necessary, use a car-washing brush or white pad as an aid. If the red colour changes into a yellowish white colour before the desired end result is achieved, Chalk-Cementex-Ex must be reapplied. After use, rinse thoroughly with water until a neutral surface is obtained. Chalk-Cement-Ex Concentrate applications, such as in refill spray bottle, dilute in the mixture ration of 150 ml Chalk-Cement-Ex Concentrate to 350 ml clean water. First, try out a test surface.

PODMIENKY APLIKÁCIE

Minimum ambient temperature: 5 °C

Maximum relative humidity: 100%

Minimum surface temperature: 5 °C

Maximum surface temperature: 35 °C

ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with clean water immediately after use.

POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

1

SKLADOVATEĽNOSŤ

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu