



**PROCHEMKO**



## KURALTEX NL 320

# Neutral cleaner for all types of surfaces

- Effective removal of atmospheric dirt
- Concentrated formula, can be diluted to a max. of 1 : 20
- Ideal for regular maintenance of coated surfaces
- Biodegradable
- Suitable for window frames, plastic, floors etc.

# KURALTEX NL 320

## POPIS PRODUKTU (DLOUHÝ)

Concentrated neutral cleaner based on surfactants, ideal for the regular maintenance of coated surfaces.

## DOPORUČENÉ POUŽITÍ

Kuraltex NL 320 is suitable for cleaning coated surfaces, plastic surfaces and anodised aluminium before finishing them with Kuraltex LP 312, Kuraltex RB 313 or Kuraltex BL 314.

## DOPORUČENÝ SYSTÉM

Pre-treatment : Kuraltex N320  
First layer : Kuraltex LP 312

Pre-treatment : Kuraltex NL 320  
First layer : Kuraltex RB 313

Pre-treatment : Kuraltex NL 320  
First layer : Kuraltex BL 314 or KuraltexPrimer  
Second layer : Kuraltex BL 314

## TEORETICKÁ SPOTŘEBA

Approx 10 m<sup>2</sup>/l.

## PRAKTICKÁ SPOTŘEBA

Consumption depends heavily on the amount of dirt.

## NÁVOD K POUŽITÍ

- Cleaning: Dilute Kuraltex NL 320 to a maximum of 1:5, depending on the level of pollution
- Periodic washing: Dilute Kuraltex NL 320 with water to a maximum of 1:20
- Apply the product using a sponge, misting nozzle or manual low pressure nozzle and allow to work for a few minutes
- Do not allow the product to dry out
- Rinse or spray off with clean water
- A car washing brush or white pad may be used to help

## PODMÍNKY POUŽITÍ

Minimum ambient temperature: 5°C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5°C.  
Maximum surface temperature: 30°C.

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with clean water directly after use.

## POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

7,50

## DOBA POUŽITELNOSTI

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu