



PROCHEMKO



KURALTEX NL 320

Neutral cleaner for all types of surfaces

- Effective removal of atmospheric dirt
- Concentrated formula, can be diluted to a max. of 1 : 20
- Ideal for regular maintenance of coated surfaces
- Biodegradable
- Suitable for window frames, plastic, floors etc.

KURALTEX NL 320

POPIS PRODUKTU (DLHÝ)

Concentrated neutral cleaner based on surfactants, ideal for the regular maintenance of coated surfaces.

ODPORÚČANÉ POUŽITIE

Kuraltex NL 320 is suitable for cleaning coated surfaces, plastic surfaces and anodised aluminium before finishing them with Kuraltex LP 312, Kuraltex RB 313 or Kuraltex BL 314.

ODPORÚČANÝ SYSTÉM

Pre-treatment : Kuraltex N320
First layer : Kuraltex LP 312

Pre-treatment : Kuraltex NL 320
First layer : Kuraltex RB 313

Pre-treatment : Kuraltex NL 320
First layer : Kuraltex BL 314 or KuraltexPrimer
Second layer : Kuraltex BL 314

TEORETICKÁ SPOTREBA

Approx 10 m²/l.

PRAKTICKÁ VÝDATNOSŤ

Consumption depends heavily on the amount of dirt.

NÁVOD NA POUŽITIE

- Cleaning: Dilute Kuraltex NL 320 to a maximum of 1:5, depending on the level of pollution
- Periodic washing: Dilute Kuraltex NL 320 with water to a maximum of 1:20
- Apply the product using a sponge, misting nozzle or manual low pressure nozzle and allow to work for a few minutes
- Do not allow the product to dry out
- Rinse or spray off with clean water
- A car washing brush or white pad may be used to help

PODMIENKY APLIKÁCIE

Minimum ambient temperature: 5°C
Maximum relative humidity : 100%
Minimum surface temperature : 5°C.
Maximum surface temperature: 30°C.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with clean water directly after use.

POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

7,50

SKLADOVATEĽNOSŤ

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu