



## MURODEX BIO

# Environmentally friendly, effective façade cleaner

- Powerful dirt dissolver without acids or solvents
- Environment and user-friendly
- Also works at lower temperatures
- For concrete, masonry, washable gravel grids, and mineral decorative plasters
- Economical to use

# MURODEX BIO

## POPIS PRODUKTU (DLOUHÝ)

A water-based façade cleaner based on special bacteria and enzyme cultures for environmentally friendly and acid-free and alkaline-free cleaning of mineral construction materials.

## DOPORUČENÉ POUŽITÍ

Murodex Bio is a special cleaner for mineral construction materials, such as building brick, concrete, natural stone, washed gravel plates, and cement-based stucco layers, and is very suitable for cleaning mineral stucco layers in façade insulation systems.

## NÁVOD K POUŽITÍ

Dilute Murodex Bio with water maximally to a ratio of 1:3 depending on the degree of fouling.

Apply and saturate with Murodex Bio using the plastic pressurised sprayer, a square brush, or hand brush.

Wipe the chosen surface with a hard brush.

Allow all of it to soak in for at least 48 hours.

After the soak in period, spray off with a high-pressure cleaner.

Before use, we recommend trying out a test surface to help determine consumption and efficacy on a specific surface and determine fouling.

## PODMÍNKY POUŽITÍ

Minimum ambient temperature : 10 °C

Maximum relative humidity : 100%

Minimum surface temperature : 10 °C

Maximum surface temperature: 35 °C

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with clean water immediately after use.

## POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

7

## DOBA POUŽITELNOSTI

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu