



MURODEX BIO

Environmentally friendly, effective façade cleaner

- Powerful dirt dissolver without acids or solvents
- Environment and user-friendly
- Also works at lower temperatures
- For concrete, masonry, washable gravel grids, and mineral decorative plasters
- Economical to use

MURODEX BIO

POPIS PRODUKTU (DLHÝ)

A water-based façade cleaner based on special bacteria and enzyme cultures for environmentally friendly and acid-free and alkaline-free cleaning of mineral construction materials.

ODPORÚČANÉ POUŽITIE

Murodex Bio is a special cleaner for mineral construction materials, such as building brick, concrete, natural stone, washed gravel plates, and cement-based stucco layers, and is very suitable for cleaning mineral stucco layers in façade insulation systems.

NAVOD NA POUŽITIE

Dilute Murodex Bio with water maximally to a ratio of 1:3 depending on the degree of fouling.

Apply and saturate with Murodex Bio using the plastic pressurised sprayer, a square brush, or hand brush.

Wipe the chosen surface with a hard brush.

Allow all of it to soak in for at least 48 hours.

After the soak in period, spray off with a high-pressure cleaner.

Before use, we recommend trying out a test surface to help determine consumption and efficacy on a specific surface and determine fouling.

PODMIENKY APLIKÁCIE

Minimum ambient temperature : 10 °C

Maximum relative humidity : 100%

Minimum surface temperature : 10 °C

Maximum surface temperature: 35 °C

ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with clean water immediately after use.

POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

PH

7

SKLADOVATEĽNOSŤ

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu