



PROCHEMKO



POLITEX

Concentrated floor wax for refreshing old linoleum

- Effective dirt and water repellence
- Restores shine
- Good wear resistance
- Resists UV, does not yellow
- Ideal for old or worn linoleum

POLITEX

POPIS PRODUKTU (DLOUHÝ)

A concentrated floor wax based on acrylate polymers, special waxes and other additives for rubber, linoleum, unglazed floor tiles, concrete floors, washed gravel tile floors and cork.

DOPORUČENÉ POUŽITÍ

Shiny floor wax for synthetic floors such as rubber, linoleum and such like, unglazed floor tiles, concrete floors, coated floors, washed gravel tile floors and cork. (not to be used on Pegulan, Mipolan or wooden floors)

TECHNICAL DATA

Hustota (g/cm³): 1,02 kg/l
Obsah pevných látek v objemu: 21%

DRY TIMES BY 20

Dotykem suché: 30 min
Suché na manipulaci: 1.5 h

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

100 µm (undiluted), 80 µm (diluted)

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

20 µm (undiluted), 10 µm (diluted)

TEORETICKÁ SPOTŘEBA

10 m²/l. (undiluted)

PRAKTICKÁ SPOTŘEBA

In practice the consumption depends on the roughness of the surface and the desired appearance.

PŘÍPRAVA POVRCHU

Dust off the surface and make it clean and dry.

NÁVOD K POUŽITÍ

Dilute Politex with water to a maximum of 1 : 2.5 (too much dilution hinders film formation). Apply the product in two layers, crossways, using a soaper. Allow the first layer to dry for at least 6 -8 hours before applying the second layer. To acquire the best possible shine use Politex diluted with water in the ratio 1 : 2.5 and apply with the help of a misting nozzle and a high speed machine. (minimum 2000 t/min)

PODMÍNKY POUŽITÍ

Minimum ambient temperature: 10°C
Maximum relative humidity: 90%
Minimum surface temperature: 10°C
Maximum surface temperature: 35°C

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with clean water directly after use.

POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

8

DOBA POUŽITELNOSTI

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu