



PREVOSIL GB

Impregnation cream for hydrophobic sealant

- Meticulous work possible without taping
- Penetrates deep into the pores of the surface
- Usable on fresh dry pointing
- Reduces efflorescence of salts and lime
- Ideal for masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone

PREVOSIL GB

POPIS PRODUKTU (DLOUHÝ)

A pasty water-based hydrophobic sealant based on silanes/siloxanes for application using brush, roller, or airless to be able to work accurately without taping off areas.

DOPORUČENÉ POUŽITÍ

Pasty hydrophobic sealant for use on masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone.

TECHNICAL DATA

Hustota (g/cm³): 1,02 kg/l
Obsah pevných látek v hmotnosti: 12%

DRY_TIMES_BY_20

Dotykem suché: N/A
Suchý nátěr: yes
Plně vytvrzené: N/A

TEORETICKÁ SPOTŘEBA

0,1 – 0,3 kg/m²

PRAKTICKÁ SPOTŘEBA

We recommend that before starting work you carry out a test to assess the rate of consumption.

PŘÍPRAVA POVRCHU

The surfaces to be treated must be free of dust and grease.

Prevosil® Special GB does not fill gaps, so any joints in poor condition should be repaired beforehand.

If necessary, treat sanded surfaces beforehand.

Apply a full layer allowing for the porosity of the surface. Apply working from the bottom to the top.

Before applying, protect surrounding materials, such as window sashes, windows, and plants.

Apply Prevosil® Special GB using a roller or brush, or by airless spraying.

PODMÍNKY POUŽITÍ

Minimum ambient temperature : 10 °C
Maximum relative humidity : 100%
Minimum surface temperature : 10 °C
Maximum surface temperature: 25 °C

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with water immediately after use.

POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

7

DOBA POUŽITELNOSTI

Can be kept for a minimum of 6 months in a cool, dry and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu