



## PREVOSIL GB

# Impregnation cream for hydrophobic sealant

- Meticulous work possible without taping
- Penetrates deep into the pores of the surface
- Usable on fresh dry pointing
- Reduces efflorescence of salts and lime
- Ideal for masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone

# PREVOSIL GB

## POPIS PRODUKTU (DLHÝ)

A pasty water-based hydrophobic sealant based on silanes/siloxanes for application using brush, roller, or airless to be able to work accurately without taping off areas.

## ODPORÚČANÉ POUŽITIE

Pasty hydrophobic sealant for use on masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone.

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 1,02 kg/l  
Obsah pevných látok v hmotnosti: 12%

## DRY TIMES BY 20

Na dotyk suché: N/A  
Suchý na opätovné natieranie: yes  
Úplne vytvrdnuté: N/A

## TEORETICKÁ SPOTREBA

0,1 – 0,3 kg/m<sup>2</sup>

## PRAKTICKÁ VÝDATNOSŤ

We recommend that before starting work you carry out a test to assess the rate of consumption.

## PRÍPRAVA POVRCHU

The surfaces to be treated must be free of dust and grease.

Prevosil® Special GB does not fill gaps, so any joints in poor condition should be repaired beforehand.

If necessary, treat sanded surfaces beforehand.

Apply a full layer allowing for the porosity of the surface. Apply working from the bottom to the top.

Before applying, protect surrounding materials, such as window sashes, windows, and plants.

Apply Prevosil® Special GB using a roller or brush, or by airless spraying.

## PODMIENKY APLIKÁCIE

Minimum ambient temperature : 10 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 10 °C  
Maximum surface temperature: 25 °C

## ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with water immediately after use.

## POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

7

## SKLADOVATEĽNOSŤ

Can be kept for a minimum of 6 months in a cool, dry and frost-free environment in the original unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu