



## PREVOSIL SPECIAAL PL

# Hydrophobic solution, less harmful to the environment

- Suitable for fresh grouting
- Penetrates deep into the surface
- Vapour-permeable system prevents frost damage
- Alkali resistant
- Ideal for brick, concrete, natural stone, aerated concrete and more



# PREVOSIL SPECIAAL PL

## POPIS PRODUKTU (DLOUHÝ)

Solution of hydrophobic treatment based on silanes/siloxanes which can be used to make mineral porous surfaces such as bricks, concrete, asbestos cement, calcium silicate, pointing mortars, aerated concrete, etc. water-repellent.

## DOPORUČENÉ POUŽITÍ

Hydrophobic treatment for use on brickwork, concrete, calcium silicate, mineral grouting and lightly porous natural stone.

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 1,0 kg/l  
Obsah pevných látek v hmotnosti: 5%

## DRY TIMES BY 20

Dotykem suché: N/A  
Suchý nátěr: N/A  
Plně vytvrzené: N/A

## TEORETICKÁ SPOTŘEBA

0.7 - 2 m<sup>2</sup>/l

## PRAKTICKÁ SPOTŘEBA

We advise carrying out a test before commencing activity in order to assess the right consumption level.

## NÁVOD K POUŽITÍ

The surfaces to be treated need to be free of dust and grease. Prevosil® Special PI does not fill gaps; any pointing in poor condition should be repaired beforehand. Any silted surfaces should first be treated with Prevosil® CE. Application in two layers wet in wet, taking account of the surface's absorbency, and apply from bottom to top. During application, protect material in the vicinity, such as window frames, windows and plants. Apply Prevosil® Special PL using the flow-coat system (low pressure avoiding mist formation).

## PODMÍNKY POUŽITÍ

Minimum ambient temperature: 5°C  
Maximum relative humidity: 100%  
Minimum surface temperature: 5°C  
Maximum surface temperature: 35°C

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with water directly after use.

## POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

7

## DOBA POUŽITELNOSTI

Can be stored for a minimum of 6 months in a cool, dry and frost-free environment in the original, unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu