



PREVOSIL SPECIAAL PL

Hydrophobic solution, less harmful to the environment

- Suitable for fresh grouting
- Penetrates deep into the surface
- Vapour-permeable system prevents frost damage
- Alkali resistant
- Ideal for brick, concrete, natural stone, aerated concrete and more



PREVOSIL SPECIAAL PL

BESKRIVELSE

Solution of hydrophobic treatment based on silanes/siloxanes which can be used to make mineral porous surfaces such as bricks, concrete, asbestos cement, calcium silicate, pointing mortars, aerated concrete, etc. water-repellent.

ANBEFALET BRUG

Hydrophobic treatment for use on brickwork, concrete, calcium silicate, mineral grouting and lightly porous natural stone.

TEKNISK DATA

Tæthed:	1,0 kg/l
Faststofindhold i vægt:	5%

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør:	N/A
Genbehandlingstør:	N/A
Fuld hærdet:	N/A

TEORETISK FORBRUG

0.7 - 2 m²/l

PRAKTISK FORBRUG

We advise carrying out a test before commencing activity in order to assess the right consumption level.

BRUGSANVISNING

The surfaces to be treated need to be free of dust and grease. Prevosil® Special PI does not fill gaps; any pointing in poor condition should be repaired beforehand. Any silted surfaces should first be treated with Prevosil® CE. Application in two layers wet in wet, taking account of the surface's absorbency, and apply from bottom to top. During application, protect material in the vicinity, such as window frames, windows and plants. Apply Prevosil® Special PL using the flow-coat system (low pressure avoiding mist formation).

ANVENDELSESBETINGELSER

Minimum ambient temperature: 5°C
Maximum relative humidity: 100%
Minimum surface temperature: 5°C
Maximum surface temperature: 35°C

RENGØRING AF UDSTYR/SPILD

Rinse with water directly after use.

BEMÆRKNINGER

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

7

HOLDBARHED

Can be stored for a minimum of 6 months in a cool, dry and frost-free environment in the original, unopened packaging.

Udstedelsesdato: 15/05/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shandon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95522 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu