



PREVOSIL SPECIAAL LOW ODOUR

**Makes mineral surfaces such as
façades water repellent**

- Strongly hydrophobic
- Colourless and almost invisible once dry
- Low-scent
- Vapour permeable system prevents frost damage
- Ideal for brick, concrete, natural stone, aerated concrete and more

PREVOSIL SPECIAAL LOW ODOUR

POPIS PRODUKTU (DLOUHÝ)

Low-scent hydrophobic treatment based on an oligomeric siloxane, dissolved in an aliphatic hydrocarbon for mineral, porous surfaces.

DOPORUČENÉ POUŽITÍ

On all mineral construction materials such as concrete, natural stone, brick, mineral grouting and stone-like panels. Prevents or reduces white salt efflorescence, frost damage, limescale contamination and surface erosion.

TECHNICAL DATA

Hustota (g/cm³):	0,8 kg/l
Obsah pevných látek v hmotnosti:	5,5%

DRY_TIMES_BY_20

Dotykem suché:	N/A
Suchý nátěr:	N/A
Plně vytvrzené:	N/A

TEORETICKÁ SPOTŘEBA

0,7 - 2 m²/l

PRAKTIČKÁ SPOTŘEBA

A test should be completed before carrying out the entire project.

NÁVOD K POUŽITÍ

The surfaces to be treated need to be free of dust and grease. Damage to the surface needs to be repaired beforehand. Apply Prevosil Special RK in two layers wet in wet, taking into account of the surface's absorbency, working to saturate from bottom to top. Avoid using when in full sun and at high temperatures. When in use, avoid smoking and proximity to an open fire. During application, protect material in the vicinity, such as window frames, windows and plants.

PODMÍNKY POUŽITÍ

Minimum ambient temperature: 5°C
Maximum relative humidity: 80%
Minimum surface temperature: 5°C
Maximum surface temperature: 25°C

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with water directly after use.

POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

DOBA POUŽITELNOSTI

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu