

PROCHEMKO



R.A.P.P. WB

Paint and Coating stripper also for indoor use

- Powerful paint stripper
- Water based
- For almost all surfaces
- Methylene chloride free

WWW.PROCHEMKO.EU

R.A.P.P. WB

POPIS PRODUKTU (DLOUHÝ)

For the quick and efficient removal of just about all paint types.
Also removes bitumen, adhesives, old wax layers, aerosol paints, and graffiti.
For use on just about all surfaces.
R.A.P.P. WB is water-based and suitable for indoor use.

DOPORUČENÉ POUŽITÍ

R.A.P.P. WB is suitable for removing Alkyd paint, water-based paints, two-component epoxyethane and polyurethane coatings, and one-component polyurethane coatings. For use on almost all surfaces.
Not for use on non-ferrous metal surfaces.
With plastic and polyester, always try out a test surface.

TEORETICKÁ SPOTŘEBA

1 - 3 m²/kg

PRAKTICKÁ SPOTŘEBA

Consumption is highly dependent on the layer thickness of the paint coating and the roughness of the surface.

NÁVOD K POUŽITÍ

Apply a generous layer of the product on the surface to be treated.
Let the product soak in for at least 30 minutes.
Remove the paint remnants using a scraper, spatula, or, in the event of graffiti, a white pad.
If necessary, repeat the treatment.
When removing multiple paint layers, cover the R.A.P.P. Cover WB with plastic foil and allow to soak in for a few hours.
Brush or spray off with (hot) water at an appropriately high pressure.
After removing the old paint, clean the treated surface using Rodex diluted with water (1:10).

PODMÍNKY POUŽITÍ

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C
Low temperatures can slow down the working of the stripper.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with water immediately after use, but with thinner if dried out.

POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

PH

3

DOBA POUŽITELNOSTI

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu