

PROCHEMKO



R.A.P.P. WB

Paint and Coating stripper also for indoor use

- Powerful paint stripper
- Water based
- For almost all surfaces
- Methylene chloride free

WWW.PROCHEMKO.EU

R.A.P.P. WB

BESKRIVELSE

For the quick and efficient removal of just about all paint types.
Also removes bitumen, adhesives, old wax layers, aerosol paints, and graffiti.
For use on just about all surfaces.
R.A.P.P. WB is water-based and suitable for indoor use.

ANBEFALET BRUG

R.A.P.P. WB is suitable for removing Alkyd paint, water-based paints, two-component epoxyethane and polyurethane coatings, and one-component polyurethane coatings. For use on almost all surfaces.
Not for use on non-ferrous metal surfaces.
With plastic and polyester, always try out a test surface.

TEORETISK FORBRUG

1 - 3 m²/kg

PRAKTISK FORBRUG

Consumption is highly dependent on the layer thickness of the paint coating and the roughness of the surface.

BRUGSANVISNING

Apply a generous layer of the product on the surface to be treated.
Let the product soak in for at least 30 minutes.
Remove the paint remnants using a scraper, spatula, or, in the event of graffiti, a white pad.
If necessary, repeat the treatment.
When removing multiple paint layers, cover the R.A.P.P. Cover WB with plastic foil and allow to soak in for a few hours.
Brush or spray off with (hot) water at an appropriately high pressure.
After removing the old paint, clean the treated surface using Rodex diluted with water (1:10).

ANVENDELSBETINGELSER

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C
Low temperatures can slow down the working of the stripper.

RENGØRING AF UDSTYR/SPILD

Rinse with water immediately after use, but with thinner if dried out.

BEMÆRKNINGER

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

PH

3

HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Udstedelsesdato: 16/05/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu