



REMOVEX GREEN

Effective and quick gel graffiti and adhesive remover

- Much more effective than other paint strippers on the market
- Gel formula is more effective than liquid alternatives
- Usable at low temperatures down to 0 °C
- Also removes glue residues
- Remove all types of paint, even 2K paints

REMOVEX GREEN

POPIS PRODUKTU (DLHÝ)

A powerful fast-acting stripper and graffiti remover in gel-paste form that does not contain methylene chloride. It removes graffiti, paint and varnish layers, and glue residues.

ODPORÚČANÉ POUŽITIE

Removex Green is suitable for removing graffiti, paint and varnish layers, epoxy resins, polyurethane resins, polymer dispersions, concrete paints and traffic stripes, as well as for cleaning various types of stones.

TEORETICKÁ SPOTREBA

1 - 3 m²/kg

PRAKTIČKÁ VÝDATNOSŤ

Consumption is heavily dependent on the degree of fouling and the type of surface.

NÁVOD NA POUŽITIE

Use Removex Green as supplied.

Carefully open the packaging.

Apply the product using a brush.

Distribute the product thickly on the surface to be treated.

Allow the product to soak in for a maximum of 30 minutes (at 20 °C).

When removing multiple paint layers, cover the Removex Green with a plastic foil.

Brush or rinse off with (warm) water at an appropriately high pressure.

If needed, repeat the treatment.

Once the old paint is removed, dilute Rodox with water (1:10) and apply it to the treated surface.

PODMIENKY APLIKÁCIE

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with clean water immediately after use.

POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

SKLADOVATEĽNOSŤ

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu