

**PROCHEMKO**



## SARDEX GREEN

# Removes atmospheric fouling, rust, salts, and lime deposits

- Effective cleaner for surfaces made of concrete, concrete blocks, and bricks
- Descaling agent and rust remover
- Extremely fast action
- Does not contain hydrochloric acid
- Biodegradable

# SARDEX GREEN

## BESKRIVELSE

A highly-concentrated liquid acid cleaner based on modified organic acids for mineral construction materials, such as concrete blocks, brick, and mineral plasters; also usable as a descaler and rust dissolver.

## ANBEFALET BRUG

Sardex Green is suitable for removing atmospheric fouling, rust, and salt efflorescence from masonry and concrete, and a variety of types natural stone.

Also suitable for removing limescale in showers, toilets, saunas and on tiles.

## PRAKTISK FORBRUG

Consumption is greatly dependent on the amount of dirt, dilution, and type of surface.

## BRUGSANVISNING

Wet the surface with water.

Dilute Sardex Green with water maximally to a ratio of 1:5.

Apply the product using a brush, cloth, or brush.

Let the product soak in for about 20 to 30 minutes.

Rinse off thoroughly with water.

## ANVENDELSBETINGELSER

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

## RENGØRING AF UDSTYR/SPILD

Rinse with clean water immediately after use.

## BEMÆRKNINGER

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

1

## HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Udstedelsesdato: 16/05/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)