



## STICKER-EX

# Removes stickers and sticker remains

- Effective action and result
- For almost all surfaces
- Wide range of use
- Handy aerosol

# STICKER-EX

## BESKRIVELSE

To remove stickers and sticker remains.  
Penetrates deep into the adhesive and dissolves it.  
Also suitable for the removal of rubber streaks (from car tyres and shoe soles), silicon residues, etc.

## ANBEFALET BRUG

This agent removes stickers, adhesive residues, rubber streaks and glue, tape, tar splashes, silicon residues, uncured PUR, grease stains, oil, heel prints, tyre marks, and so on from almost all thick non-porous surfaces.

## TEORETISK FORBRUG

4 – 15 m<sup>2</sup>/l

## PRAKTISK FORBRUG

The consumption is heavily dependent on the surface and type of label or sticker.

## BRUGSANVISNING

Apply Sticker-Ex using the aerosol on the surface to be treated.  
Let it soak in for a few minutes depending on the weather conditions, surface, and type of sticker.  
Spray the adhesive remnants from removed stickers again and then remove with a cloth or paper.  
Scratch open plastic stickers and ordinary stickers with a waterproof finishing layer.  
If possible, rinse off the surface with plenty of water.  
Always test on a part of the surface to be treated to assess whether the product is compatible with the surface.

## ANVENDELSESBETINGELSER

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5 °C  
Maximum surface temperature: 35 °C  
Low temperatures can slow down the working of the product.

## RENGØRING AF UDSTYR/SPILD

Rinse with water immediately after use.

## BEMÆRKNINGER

Dispose of the product residue, waste from removing graffiti, and empty packaging as chemical waste in accordance with the local regulations and legal provisions.

## PH

9,50

## HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Udstedelsesdato: 16/05/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europas anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)