



STO-NEX 4

Floor impregnation with colour enhancing effect

- Penetrates deep into the surface to be treated
- Beautiful 'wet look' improves the appearance of weathered stone
- Highly grease and oil repellent
- Ideal for natural stone
- Does not affect anti-slip properties

STO-NEX 4

POPIS PRODUKTU (DLHÝ)

A hydrophobic and oleophobic agent based on alcohols that protects porous stone and stony surfaces and provides a wet look.

ODPORÚČANÉ POUŽITIE

Sto-Nex 4 is used to protect natural stone, such as sandstone, terrazzo, limestone, blue stone, granite etc.

DRY TIMES BY 20

Na dotyk suché: N/A
Suchý na opätovné natieranie: N/A
Úplne vytvrdnuté: N/A

PRAKTICKÁ VÝDATNOSŤ

Consumption is heavily dependent on the absorptive capacity of the surface.

NÁVOD NA POUŽITIE

Degrease, clean, and dry the surface.
Avoid leaving cleaning chemicals residues.
Shake Sto-nex 4 before use.
Use this product as supplied.
Apply the product wet in one layer and ensure the surface is saturated.
Avoid over saturating.
Use a (wide) brush or squeegee.
Use a clean and grease-free tool.

PODMIENKY APLIKÁCIE

Minimum ambient temperature : 5 °C
Maximum relative humidity : 80%
Minimum surface temperature : 5 °C
Maximum surface temperature: 30 °C

ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with Isopropyl Alcohol immediately after use.

POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

SKLADOVATEĽNOSŤ

Can be kept for a minimum of 6 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu