



TOPPER

Universal graffiti remover for non-porous surfaces

- Rapid and thorough action
- Usable in enclosed spaces
- Removes ink, aerosol paints, and wax dyes
- Does not damage most surfaces
- Ideal in combination with Prochemko permanent anti-graffiti systems

TOPPER

BESKRIVELSE

A universal user-friendly graffiti remover for almost all non-porous surfaces. Quickly and thoroughly removes virtually all graffiti.

ANBEFALET BRUG

This cleaning agent removes almost all graffiti and daubing on thick non-porous surfaces. Safe on almost all surfaces, such as thermo-hardened plastics, coated surfaces, trapezoidal sheets with plastisol, Trespa, Lexane, and Plexiglas, and all surfaces with an anti-graffiti coating.

TEORETISK FORBRUG

4 – 15 m²/l

PRAKTISK FORBRUG

The actual efficiency is heavily dependent on the surface and type of graffiti.

BRUGSANVISNING

Apply Topper with a brush, sponge, or sprayer on the surface to be treated.

Let it soak in for a few minutes depending on the weather conditions, surface, and graffiti.

Once the graffiti is dissolved, remove it with a cloth or sponge.

Wipe with a non-woven white nylon pad to improve the effectiveness.

If possible, rinse off the surface with plenty of water.

When cleaning using graffiti removers, the stain will usually increase in size on most surfaces.

To prevent this from happening, we recommend that you first treat the surface with Rodex (1:10). This will prevent the dissolved graffiti from setting again.

Always test on a part of the surface to be treated to check whether the product is compatible with the surface.

ANVENDELSESBETINGELSER

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

Low temperatures can slow down the working of the product.

RENGØRING AF Udstyr/SPILD

Rinse with water immediately after use.

BEMÆRKNINGER

Dispose of the product residue, waste from removing graffiti, and empty packaging as chemical waste in accordance with the local regulations and legal provisions.

PH

12

HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Udstedelsesdato: 16/05/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europas anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu