



TOPPER GEL

Pasty stripper for porous surfaces

- Penetrates deep into the surface
- Usable in enclosed spaces
- Removes ink, aerosol paints, and wax dyes
- Does not damage most surfaces
- Pasty product does not run off the wall



TOPPER GEL

POPIS PRODUKTU (DLOUHÝ)

User-friendly pasty graffiti cleaner for removing daubs, ink, and paint on porous surfaces.

DOPORUČENÉ POUŽITÍ

This is agent removes almost all graffiti and daubing on non-porous surfaces. Safe on almost all surfaces, such as plastics, coated metals, trapezoidal sheets with plastisol, Trespa, Lexane, and Plexiglas, and all surfaces with an anti-graffiti coating.

TEORETICKÁ SPOTŘEBA

4 – 15 m²/l

PRAKTIČKÁ SPOTŘEBA

The actual efficiency is heavily dependent on the surface and type of graffiti.

NÁVOD K POUŽITÍ

Apply Topper Gel to the surface to be treated using a brush or roller. Let it soak in for a few minutes depending on the weather conditions, surface, and graffiti. Once the graffiti is dissolved, remove it with a cloth or sponge. Wipe with a non-woven white nylon pad to improve the effectiveness. If possible, rinse off surfaces with lots of water. When cleaning using graffiti removers, the stain will usually increase in size on most surfaces. To prevent this from happening, we recommend that you first treat the surface with Rodex (1:10). This will prevent the dissolved graffiti from setting again. Always test on a part of the surface to be treated to check whether the product is compatible with the surface.

PODMÍNKY POUŽITÍ

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C
Low temperatures can slow down the working of the product.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with water immediately after use.

POZNÁMKY

Dispose of the product residue, waste from removing graffiti, and empty packaging as chemical waste in accordance with the local regulations and legal provisions.

PH

12

DOBA POUŽITELNOSTI

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu