

**PROCHEMKO**



## UNIVERSOL® CONCENTRATE

# Cleans and degreases paintwork and more

- Anti-static
- No need to rinse afterwards
- Biodegradable
- Low foaming

[WWW.PROCHEMKO.EU](http://WWW.PROCHEMKO.EU)

# UNIVERSOL® CONCENTRATE

## BESKRIVELSE

For cleaning, degreasing and making surfaces anti-static before painting. Also very suitable as universal cleaner for cleaning slats, windows, floors, doors, carpets, gas cookers, window frames etc. Also removes nicotine deposits.

## ANBEFALET BRUG

Universol is very suitable for degreasing and making surfaces antistatic before for painting. Due to the good properties of this product, the substrate no longer needs to be washed, so that painting can be started immediately. In adapted dilution grade suitable for cleaning floors, windows, engines and household equipment etc.

## TEORETISK FORBRUG

10 - 100 m<sup>2</sup>/liter

## PRAKTISK FORBRUG

Depending on the degree of dilution, the substrate and the pollution.

## BRUGSANVISNING

Dilute Universol with water up to 1:100, depending on the application. Apply the product using a sponge, cloth or brush. In case of heavy pollution, adjust concentration and/or repeat treatment. To refill the sprayer bottle dilute the Universol concentrate in the mixing ratio of 150 ml Universol concentrate and 500 ml clean water. First fill the bottle with the water to the desired level, then add the Universol concentrate.

## ANVENDELSBETINGELSER

Can be used in almost all circumstances, do not apply in direct sunlight and under frost conditions.

## RENGØRING AF UDSTYR/SPILD

Immediately after use with water

## PH

11,27

## HOLDBARHED

Minimum of 12 months, if stored in a dry, cool and frost-free room in unopened, original packaging.

Udstedelsesdato: 20/11/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)