

PROCHEMKO



UNI-WASH HD

Economical concentrated cleaner with hardness stabilisers

- Removes grease, road grime, and atmospheric deposits
- No risk of limescale crust in machines
- Usable in hard water
- For use on plastics, metals, coatings, concrete, and tiles
- Economical concentrated formula

UNI-WASH HD

BESKRIVELSE

A highly-concentrated cleaner based on anionic and non-ionic surfactants and hardness stabilisers for use on plastics, metals, cured lacquers, floors, such as concrete and tiles.

ANBEFALET BRUG

Uni-Wash H.D. is used to remove street grime, atmospheric deposits from vehicles, and dirty and/or greasy floors.

By adding hardness stabilisers, the product can be used in extremely hard water in high-pressure equipment, and other cleaning equipment, without the risk of limescale crust in the spray heads or dosing systems.

Also suitable for use on plastics, rubber, cured varnishes, floors with a variety of structures, and most metals.

PRAKTISK FORBRUG

Consumption is heavily dependent on the degree of dilution, the surface, and the degree of fouling.

BRUGSANVISNING

Uni-Wash H.D. is used in floor cleaning machines, spray equipment, high-pressure cleaners, and also by hand.

Floor cleaning : ratio of 1 to 50/100 depending on the type of dirt the dosing tank.

Spray equipment : 5% solution in water, spray the object and then, after a few minutes, spray off with a powerful water jet.

High-pressure equipment: 10% solution in the dosing tank.

Adjust the dose so that you spray with a 0.5% solution.

Rinse with water.

With stubborn dirt, we recommend that you allow the product to soak in longer.

ANVENDELSBETINGELSER

Can be used in all circumstances, but do not use in full sunlight or in frosty conditions.

RENGØRING AF Udstyr/SPILD

Rinse with water immediately after use.

BEMÆRKNINGER

Dispose of remaining product, empty packaging, and waste water as chemical waste in accordance with the local regulations and legal requirements.

PH

9,50

HOLDBARHED

Can be kept for a minimum of 12 months when stored in a dry, cool and frost-free environment in the original unopened packaging.

Udstedelsesdato: 25/03/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu