

**PROCHEMKO**



## UNI-WASH HD

# Economical concentrated cleaner with hardness stabilisers

- Removes grease, road grime, and atmospheric deposits
- No risk of limescale crust in machines
- Usable in hard water
- For use on plastics, metals, coatings, concrete, and tiles
- Economical concentrated formula

# UNI-WASH HD

## POPIS PRODUKTU (DLHÝ)

A highly-concentrated cleaner based on anionic and non-ionic surfactants and hardness stabilisers for use on plastics, metals, cured lacquers, floors, such as concrete and tiles.

## ODPORÚČANÉ POUŽITIE

Uni-Wash H.D. is used to remove street grime, atmospheric deposits from vehicles, and dirty and/or greasy floors.

By adding hardness stabilisers, the product can be used in extremely hard water in high-pressure equipment, and other cleaning equipment, without the risk of limescale crust in the spray heads or dosing systems.

Also suitable for use on plastics, rubber, cured varnishes, floors with a variety of structures, and most metals.

## PRAKTICKÁ VÝDATNOSŤ

Consumption is heavily dependent on the degree of dilution, the surface, and the degree of fouling.

## NÁVOD NA POUŽITIE

Uni-Wash H.D. is used in floor cleaning machines, spray equipment, high-pressure cleaners, and also by hand.

Floor cleaning : ratio of 1 to 50/100 depending on the type of dirt the dosing tank.

Spray equipment : 5% solution in water, spray the object and then, after a few minutes, spray off with a powerful water jet.

High-pressure equipment: 10% solution in the dosing tank.

Adjust the dose so that you spray with a 0.5% solution.

Rinse with water.

With stubborn dirt, we recommend that you allow the product to soak in longer.

## PODMIENKY APLIKÁCIE

Can be used in all circumstances, but do not use in full sunlight or in frosty conditions.

## ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with water immediately after use.

## POZNÁMKY

Dispose of remaining product, empty packaging, and waste water as chemical waste in accordance with the local regulations and legal requirements.

## PH

9,50

## SKLADOVATEĽNOSŤ

Can be kept for a minimum of 12 months when stored in a dry, cool and frost-free environment in the original unopened packaging.

last\_updated: 05/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu