

**PROCHEMKO**



## VETCLEAN OS

# Strong defoaming degreaser for scrubbing machines

- Effective removal of dirt, grease and soot
- Defoaming formula is well suited to machine cleaning
- Penetrates deeply into the surface
- Cost effective cleaner

# VETCLEAN OS

## BESKRIVELSE

Highly concentrated defoaming alkaline degreaser based on surfactants, cleaning enhancers and lye for machine removal of dirt, grease, and soot and fire damage from a variety of different surfaces.

## ANBEFALET BRUG

Highly suitable for heavy duty cleaning such as the removal of deposits caused by soot and fire damage from floors, walls, furniture, etc. Also suitable for cleaning plastic (façade) panels, etc.

## TEORETISK FORBRUG

Approx 20 m<sup>2</sup>/l

## PRAKTISK FORBRUG

Consumption depends heavily on the level of dirt, dilution and type of surface.

## BRUGSANVISNING

- Dilute Vetclean OS as required with water to a maximum of 1:10
- Apply the product using a hand low-pressure nozzle, misting nozzle or scrubbing machine
- Brush off with a hard brush
- Allow the product to work for a few minutes
- Rinse or spray with clean water or by machine with clean water

## ANVENDELSESBETINGELSER

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

## RENGØRING AF UDSTYR/SPILD

Rinse with clean water directly after use.

## BEMÆRKNINGER

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

12,50

## HOLDBARHED

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Udstedelsesdato: 16/05/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)