

**PROCHEMKO**



## GREASE CLEANER

# Concentrated alkaline low-foaming degreaser

- Effectively removes dirt, grease and soot
- Also suitable for mechanical cleaning
- Penetrates deeply into the surface
- Cost effective cleaner
- Lightly foaming

# GREASE CLEANER

## OPIS

A highly-concentrated alkaline degreaser based on surfactants, cleaner enhancers, and lye to remove dirt, grease, and soot and fire damage from a variety of different surfaces.

## ZALECANE UŻYCIE

Highly suitable for heavy-duty cleaning such as the removal of deposits caused by soot and fire damage from floors, walls, furniture, etc.

Also suitable for cleaning plastic (façade) panels, etc.

## ZUŻYCIE TEORETYCZNE

Ca. 20 m<sup>2</sup>/l

## ZUŻYCIE PRAKTYCZNE

Consumption is greatly dependent on the amount of dirt, dilution, and type of surface.

## WSKAZÓWKI DOTYCZĄCE UŻYCIA

- Dilute Grease Cleaner Foam with water maximally to a ratio of 1:10
- Apply the product using a hand-held low-pressure spray gun or an atomiser
- Brush through with a hard brush
- Allow the product to soak in for a few minutes
- Rinse or spray off with clean water

## WARUNKI APLIKACJI

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

## CZYSZCZENIE NARZĘDZI / ZABRUDZEŃ

Rinse with clean water immediately after use.

## PH

12,30

## OKRES TRWAŁOŚCI PRODUKTU

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Data wydania: 05/02/2025

**Dostępne kolory i opakowania:** Więcej informacji na temat dostępnych kolorów i opakowań na stronie internetowej [www.rust-oleum.eu](http://www.rust-oleum.eu).

**Zrzeczenie się:** Informacje tu zawarte przekazywane są w dobrej wierze, bez udzielania gwarancji. Ponieważ warunki aplikacji są poza naszą kontrolą, Rust-Oleum nie może ponosić jakiegokolwiek odpowiedzialności lub obciążeń finansowych, które mogą wyniknąć z niewłaściwego zastosowania tego produktu. Produkt musi być przechowywany, transportowany i aplikowany zgodnie z zaleceniami Rust-Oleum. Użytkownik powinien zadbać o posiadanie najbardziej aktualnej karty produktu. Wszystkie karty dostępne są na stronie internetowej producenta lub dystrybutora. Firma zastrzega sobie prawo modyfikowania danych bez uprzedzenia.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu