



WENDRO

Highly powerful, strong alkaline facade cleaning paste

- Effective cleaning of mineral surfaces
- Ideal for acid-sensitive surfaces
- Removes atmospheric dirt, patina, grease, oil and paint
- Paste-like formula does not drip from the wall
- Free from carbon tetra chloride



WENDRO

POPIS PRODUKTU (DLOUHÝ)

Extremely potent, strong alkaline facade cleaning paste based on lye, surfactants, special cleaning enhancers, evaporation inhibitors for cleaning acid-sensitive mineral surfaces.

DOPORUČENÉ POUŽITÍ

Wendro is suitable for cleaning acid-sensitive, mineral surfaces, masonry, concrete, natural stone, etc.

TEORETICKÁ SPOTŘEBA

2 - 3 m²/kg

PRAKTICKÁ SPOTŘEBA

Consumption depends heavily on the level of dirt and type of surface.

NÁVOD K POUŽITÍ

- Protect alkali-sensitive areas
- Use Wendro as supplied
- Apply the product using a wide brush or hand brush
- Allow the product to work for a minimum of 30 minutes and a maximum of 36 hours
- Spray off with water under the appropriate pressure (water temperature max. 40 °C) until no more foaming occurs
- Check the pH of the surface, neutralising as required

NB: When much time is required for the product to take effect e.g. when removing paint, then we advise protecting Wendro from drying out by covering with a thin sheet of PE. After allowing to take effect first remove thick layers with a spatula before spraying off with water.

PODMÍNKY POUŽITÍ

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with clean water directly after use.

POZNÁMKY

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

14

DOBA POUŽITELNOSTI

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu