



## WENDRO

# Highly powerful, strong alkaline facade cleaning paste

- Effective cleaning of mineral surfaces
- Ideal for acid-sensitive surfaces
- Removes atmospheric dirt, patina, grease, oil and paint
- Paste-like formula does not drip from the wall
- Free from carbon tetrachloride

## BESKRIVELSE

Extremely potent, strong alkaline facade cleaning paste based on lye, surfactants, special cleaning enhancers, evaporation inhibitors for cleaning acid-sensitive mineral surfaces.

## ANBEFALET BRUG

Wendro is suitable for cleaning acid-sensitive, mineral surfaces, masonry, concrete, natural stone, etc.

## TEORETISK FORBRUG

2 - 3 m<sup>2</sup>/kg

## PRAKTIKSK FORBRUG

Consumption depends heavily on the level of dirt and type of surface.

## BRUGSANVISNING

- Protect alkali-sensitive areas
- Use Wendro as supplied
- Apply the product using a wide brush or hand brush
- Allow the product to work for a minimum of 30 minutes and a maximum of 36 hours
- Spray off with water under the appropriate pressure (water temperature max. 40 °C) until no more foaming occurs
- Check the pH of the surface, neutralising as required

NB: When much time is required for the product to take effect e.g. when removing paint, then we advise protecting Wendro from drying out by covering with a thin sheet of PE. After allowing to take effect first remove thick layers with a spatula before spraying off with water.

## ANVENDELSESBETINGELSER

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

## RENGØRING AF UDSTYR/SPILD

Rinse with clean water directly after use.

## BEMÆRKninger

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

14

## HOLDBARHED

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Udstedelsesdato: 16/05/2024

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95522 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)